

## PATENT ABSTRACTS OF JAPAN

(11) Publication number: 02126922 A

(43) Date of publication of application: 15.05.90

(51) Int. CI B01D 65/02 B01D 61/06

(21) Application number: 63277431

(22) Date of filing: 04.11.88

(71) Applicant:

MITSUI ENG & SHIPBUILD CO LTD

MATSUO YASUO SATO HIROHIKO

(54) BACK WASHING METHOD OF SEPARATING MEMBRANE

(57) Abstract:

PURPOSE: To allow easy back washing of a separating membrane by closing the valve of a discharge pipeline to nearly equalize the pressure between the internal pressure of a supply pipeline and the internal pressure of the discharge pipeline, then opening the valve of a recycle pipe to drop the internal pressure of the supply pipeline.

CONSTITUTION: An original figuid is Introduced by a supply pump 3 from an original fliguid tank 1 into a separating membrane module 2 and the filtrate separated by the module 2 is introduced into a filtrate tank 10. The recycle pipe 5 having a 1st valve 6 is connected to the supply pipes 10 to the supply pipes 10 to the supply pipes 10 to the module 2. An accumulator 7 and a 2nd valve 8 are disposed to the filtrate tank 10. This valve 8 is closed to the filtrate tank 10. This valve 8 is closed to the filtrate tank 10. This valve 8 is closed to the filtrate tank 10. This valve 8 is closed to the filtrate and 10 the supply pipeline 4 and the internal pressure of the discharge pipeline 9; thereafter, the valve 6 is opponed to drop the internal pressure of the supply pipeline 9. The valve 6 is opponed to drop the internal pressure of the supply pipeline 4. The separating membrane is back vashed by these simple.

operations.

COPYRIGHT: (C)1990,JPO&Japio

